TECH -

Covingtons Customs Firewall Cover Plate Installation

Story by Jason Mook - Photos by Jesse B. Nelson

ovingtons Customs manufactures an entire line of custom Bagger parts that set your Bagger apart from the crowd. Covingtons has a complete line of hole, finned, and dimpled custom parts for several different areas of your Bagger. When installed, they will add a touch of style and detail. Covingtons found a perfect place to add a touch of style on your Bagger: behind the motor at the "firewall" of the frame. The firewall of the frame has always been an area of the Touring models that is too plain and is always overlooked. Covingtons' Firewall Cover is very easy to install and dresses up this area of your Bagger. To see the complete line of parts available from Covingtons Customs, visit www.CovingtonsCustoms.com.

 (\blacklozenge)

Difficulty Level: 1/5 Estimated Time to Complete: 0.5 hours



Covingtons' Dimpled Firewall Plate in black with included hardware.



The 2009 Bagger with the stock "firewall" from the factory.

TOOLS & SUPPLIES NEEDED

- 1. Allen Wrenches
- 2. 7/16" Wrench

()

- 3. Needle Nose Pliers
- 4. Removable (Blue) **Thread Locker**



Remove the seat from the motorcycle.



Use a set of needle nose pliers to remove the zip tie from the frame for the spark plug wire.



Unplug the spark plug wires from the coil. The right side post is for the rear head, and the left side coil post is for the front.



Position the Firewall Plate on the frame, aligning the holes in the frame with the holes in the frame's firewall.

94 - OCTOBER 2016 www.URBANBAGGER.com

۲

COVINGTONS CUSTOMS Firewall Cover Plate Installation



Start the included hardware by hand.



۲

Using a 5/32" Allen and 7/16" wrench, tighten the hardware down uniformly.



Reinstall the spark plug wires back onto the coil. Ensure the front and rear spark plug wires are on the correct post of the coil



Capture the spark plug wires with the included bracket from Covingtons. The bracket will replace the use of zip ties to hold the spark plug wires in position.



Use the included bolt to hold the bracket to the firewall plate.



Reinstall the seat back on the motorcycle.

۲



The 2009 Bagger with Covingtons' Black Dimpled Firewall Plate installed.